

Easy Operation and High Quality Performance

Blanket Folder with built-in Feeding Clamp Units

DT-6X-C



Blanket Folder with built-in Feeding Clamp Units

DT-6X-C

Specifications

- Conveyor Speed: 35 m/min
- Power Supply: 200VAC 3φ 50Hz (Other Voltage is option)
- Electric Capacity: 2.6Kw
- Air Consumption: 5MPa(5Kg/cm²) 150 L/min

Applicable Size

- Max. Length for 2 Lateral Folding: 2200mm
- Max. Length for 3 Lateral Folding: 2200mm
- Max. Length at 1st Cross Folding: 600mm
- Max. Width: 1400mm
- Min. Width: 800mm
- Max. Thickness for 2 Cross Folding: 60mm


The standard equipment

- ◆ Selectable 2 or 3 Lateral Fold, 1 or 2 Cross Folding
 - ◆ Anti Static Bar (1 Bar)
 - ◆ 4" Color Touch Screen
- Program Change, Parameter Change, Error Display, Input/Output Check, etc.


- ◆ 30 Programs
- ◆ Language: Japanese, English, Chinese
- ◆ Safety Measure
 - Emergency Stop Switch at both sides of Folder unit
 - Safety Cover
 - Jam Detection Function. When any jam detected, the machine will be automatically stopped.

Folding Patterns and Mechanism

Lateral Folding Section



Cross Folding Section



Lateral (A) Fold = 1/2 Fold			
Lateral (B) Fold = 1/2 Fold			
Lateral (C) Fold = 1/4 Fold			
Lateral Fold Combination	1 Fold = (B)	2Fold = (A) + (B)	3 Fold = (A) + (C)
Folding Pattern			
Cross (X1) Fold = 1/2 Fold			
Cross (X2) Fold = 1/2			
Cross Fold Combination	1 Fold = (X1)	2Fold = (X1) + (X2)	
Folding Pattern			

- 1st Lateral Fold: Air Blow and Forward/Reverse Conveyor
 - 2nd and 3rd Lateral Fold: Knife
 - 1st Cross Fold: Knife and Pinch Roller
 - 2nd Cross Fold: Knife and Forward/Reverse Conveyor